



Lightweight Mobile Rises Light Height 5m

ref. M103020023

Light mobile sub-person platform with aluminum chassis. Electric lift and manual translation. Load capacity of 120/200 kg depending on model, lifting height of 2.98 meters and maximum working height of 5 meters.

CE certificate

0,00 € tax excluded

Características principales

Peso (kg)	495
Altura (mm)	1900
Descripción	Subepersonas móvil ligero 5 metros
Altura máx. (mm)	5000
Capacidad (kg)	180
Elevación total (mm)	2.900
Dimensiones (mm) largo x ancho x alto	1100 x 680 x 1900
Sistema elevador	Eléctrico
Sistema propulsor	Manual
Batería (Ah)	12V/33 Ah
Autonomía	3-4 horas
Rodillos	4 ruedas pivotantes
Dimensiones (mm) Especial	700x520
Alimentación (V)	Sist. central de bloqueo
Ruedas	Batería de Gel
Nº de ruedas delante/detrás	Con anillo en poliuretano
Ocupantes	2 / 2
Habitáculo del operador (kg)	1
Normativa	120 / 200
	CE

Características ampliadas

Description of the platform and advantages.

This new series of mobile lifting platforms is designed to be a simple and lightweight transport tool thanks to its aluminum fabrication. It is equipped with 4 swivel castors with central locking system. Its ergonomic design and small size allow easy transport both in the vehicle and in the work area. It incorporates a gel battery without maintenance of 12V / 33 Ah.

Both versions (the 120kg and the 200kg) come with doors with automatic closing.

(See attached images for more information on each model)



Advantages

- Light weight: The aluminum construction of the basket, mast and chassis and the possibility of disassembling its counterweights allows simple handling of products with reduced weight (80 kg for the 120kg version)
- Compact design: Its small size (68 x 110 x 190 for the 120 kg version) and its ergonomic handles allow the platform to be transported through doors and elevators in a very simple way.
- Removable counterweights: the 4 counterweights reduce the center of gravity during the task and are equipped with a rapid disassembly system, which allows to reduce the weight during transport.
- Operator control panel: The key control panel, lift / lower control system and emergency stop button, guarantees efficient protection IP 54 for outdoor use.
- Safety: The 4 high-strength wheels with polyurethane ring have a central locking system that is easily operated by pedal.
- Battery compartment: The access step is made of high quality and resistant aluminum sheet. It contains the gel battery, the integrated battery charger, the main and emergency switch and a button to lower the cage.

TECHNICAL SPECIFICATION

LOAD CAPACITY kg 120-200

LIFTING HEIGHT m 2.98

WORK HEIGHT m 5

MEASURES (width x height x length)

mm 680X1100X1980

WHEELS 4

MATERIAL WHEELS Polyurethane

BATTERY 12V / 39-78 Ah

PLATFORM DIMENSIONS mm 700 X 520

ELEVATION CYCLES 50,000

WEIGHT WITH COUNTERWEIGHT kg 154